



# blue photon®

## Technology & Workholding Systems

### Soak Debond Tank

Part #: 81300


The soak debond tank allows for debonding the part from the grippers without twisting. This method is preferred in applications where twist debonding could cause delamination or other damage to the workpiece.

#### Features

- Stainless steel construction
- Electric heat
- Programmable temperature control/sensor
- Simple push button cycle operation
- Easy access for clearing and maintenance
- High performance insulation to avoid heat loss
- Thermal insulation
- Easy fill and drain tank
- Low energy consumption
- Emergency stop button
- Dipping time timer
- Manual or automatic operation
- No water alarm light
- Interlock casters

#### Product Specifications

- Maximum product height: 10 inches (255 mm)
- Immersion platform size: 23 x 14" (584 x 355 mm)
- Immersion depth: 12 inches (305 mm)
- Cycle time: up to 15/min.
- Volume of water: 100 liters
- Electrical: 220V / 60 Hz / 3 Ø, 10 amps
- Machine size: 27 L x 33.5 W x 57.25 H inches (673 x 1016 x 1454 mm) with cover up (63 H inches (1600 mm))
- Weight: 394 lb (179 kg)



#### Options

208 V / 60 Hz / 3 Ø; 50 amps

#### Sales and Engineering Support

Blue Photon Technology & Workholding Systems LLC  
1002 Industrial Park Dr., Shelby, MI 49455  
855-777-2040 • sales@BluePhotonGrip.com

©2019 Blue Photon Technology & Workholding Systems LLC. All Rights Reserved. Blue Photon Technology & Workholding Systems LLC assumes no responsibility for any errors or omissions in this document. This document is for reference only and actual application will vary according to the application. Blue Photon has made every effort to ensure the accuracy of the product information in this document; however, we are not responsible for typographical discrepancies. Actual products may vary from those shown in photos. Refer to our website for current product and safety information. Blue Photon Soak Debond Tank 10242 03.11.19